

# Product Comparison:

## ARC Network Solutions with Integrated 3G/4G



ARC MBR1400 (LPE, LP3)



ARC CBA750B (LPE, LP3)



ARC CBA850 (LPE, LP3)

FEATURES		RETAIL & BRANCH: POS & FAILOVER		
WAN/LAN	WAN / LAN via ETHERNET	5* (GigE) / 5* (GigE)	0 / 1(10/100)	0 / 2 (GigE)
	SERIAL	USB-TO-SERIAL	USB-TO-SERIAL	RJ45 SERIAL or USB-TO-SERIAL
	WIRELESS BROADBAND TECHNOLOGY	LTE/HSPA+/EVDO, LTE/PA+	LTE/HSPA+/EVDO, LTE/PA+	LTE/HSPA+/EVDO, LTE/PA+
	CARRIERS SUPPORTED	ATT, INTL, SP, TMO, VZ	ATT, INTL, SP, TMO, VZ	ATT, INTL, SP, TMO, VZ
	MULTI-CARRIER SOFTWARE-DEFINED RADIO	•	•	•
	MODEM ANTENNAS (INCLUDED) & EXTERNAL PORTS	2 SMA	2 SMA	2 SMA
	24X7 MODEM CONNECTION VERIFICATION	•	•	•
	DATA USAGE MANAGEMENT & ALERTS	•	•	•
WIFI	WIFI TECHNOLOGY	a/b/g/n	N/A	N/A
	WIFI CLIENTS (SIMULTANEOUS)	128	N/A	N/A
	WIFI PERFORMANCE RATING <sup>8</sup>	★ ★ ★	N/A	N/A
	WIFI SECURITY: WEP, WPA, WPA2, WPA2 ENTERPRISE	•	N/A	N/A
	SPATIAL STREAMS, INCLUDED ANTENNAS & PORT(S)	3x3, 3 external R-SMA	N/A	N/A
	MULTIPLE SSIDS/WIFI NETWORKS	4	N/A	N/A
	WIFI AS WAN	•	N/A	N/A
MANAGEMENT	CAPTIVE PORTAL/HOTSPOT SERVICES	•	N/A	N/A
	EASY WEB-BASED LOCAL MANAGEMENT	•	•	•
	ENTERPRISE CLOUD MANAGER	•	•	•
	SNMP MANAGEMENT	V 1,2c,3	V 1,2c,3	V 1,2c,3
	COMMAND LINE INTERFACE OVER SSH	•	•	•
	SMS SUPPORT	• <sup>7</sup>	• <sup>7</sup>	• <sup>7</sup>
ADVANCED FEATURES	FAILOVER / FAILBACK / LOAD BALANCING	•	• <sup>3</sup>	• <sup>3</sup>
	OSPF/BGP/RIP <sup>9</sup> , VRRP <sup>9</sup> , STP <sup>9</sup>	• <sup>6</sup>	•	•
	IPv6 SUPPORT	•	•	•
	IP PASS-THROUGH	•	•	•
	ADVANCED QOS	•	•	•
	RADIUS OR TACACS+ ADMINISTRATIVE AUTH.	•	•	•
	802.1X ETHERNET PORT SECURITY	•	•	•
	IPSEC VPN TERMINATION & GRE TUNNELING	20	•	•
	SITE-TO-SITE DYNAMIC VPN w/NHRP <sup>9</sup> , L2TP <sup>9</sup>	• <sup>6</sup>	•	•
	OPENVPN (SSL VPN) <sup>9</sup>	•	•	•
	NEMO/DMNR SUPPORT <sup>9</sup>	•	•	•
	802.1Q VLAN SUPPORT	•	•	•
	LAN/WAN AFFINITY	•	• <sup>3</sup>	• <sup>3</sup>
STANDALONE GPS (IF SUPPORTED BY CARRIER)	• ACTIVE	• ACTIVE	• ACTIVE	
HARDWARE	SIZE, WEIGHT, MATERIAL	9x7.3x1.6-in, 1.5-lb, plastic	9x7.3x1.6-in, 1.5-lb, plastic	4.8x4.8x1.7-in, 1.5 lb, Plastic
	SIM SLOTS	2 (2FF)	2 (2FF)	2 (2FF)
	CERTIFICATIONS	FCC, IC, CE, CARRIER	FCC, IC, CE, CARRIER	FCC, IC, CE, CARRIER, INT'L
	POWER OVER ETHERNET (POE)	•	•	•
	OPERATING TEMPERATURE	0 to 40C	0 to 50C	0 to 50C

\* LAN/WAN Configurable; 3 Load balancing and LAN/WAN affinity disabled on IP PASS-THROUGH network; 4 Individual policies; 5 No GPIO; 6 Requires hardware v2.0; 7 SIM-based models with SIMs that support SMS only, additional SMS charges may apply; 8 CradlePoint rating based on throughput, range and overall performance ★=full ☆=half; 9 Requires Extended Enterprise License